

| | Type | L # | Hits | Search Text | DBs | Time Stamp | Comments | Error Definition |
|---|------|-----|-------|-----------------------|---|---------------------|----------|------------------|
| 1 | BRS | L1 | 1811 | solenoid adj driver | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:26 | | |
| 2 | BRS | L2 | 18763 | control adj portion | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:26 | | |
| 3 | BRS | L3 | 56 | 1 and 2 | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:45 | | |
| 4 | BRS | L4 | 5874 | detecting adj portion | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:44 | | |
| 5 | BRS | L5 | 442 | computing adj portion | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:53 | | |
| 6 | BRS | L6 | 45 | 4 and 5 | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:44 | | |
| 7 | BRS | L7 | 74989 | resistance adj value | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:53 | | |
| 8 | BRS | L8 | 13 | 5 and 7 | USPAT; US-PGPUB; EPO; JPO; DERWENT | 2003/08/15 10:53 | | |